



REIKER GL-1 Multipurpose Gear Lubricants

REIKER GL-1 Gear Oils are manufactured from 100% virgin base oils. They provide long life for gears and bearings in gear cases where OEM recommends the use of a straight mineral oil in SAE viscosity grades of 90, 140, and 250 weights.

REIKER GL-1 Gear Oils contain rust, corrosion and foam inhibitors, plus a pour depressant to assure fluidity of low temperatures. They are suitable for use where API Service Classification GL-1 is called for.

REIKER GL-1 Gear Oils are recommended for use in transmissions, differentials, final drives, steering gears, universal joints, spline shafts, industrial closed gears and many other miscellaneous applications in bearing and gear lubrications of equipment where GL-1 or straight mineral oil is specified.

Specifications, Approvals, and Recommendations:

- API Service GL-1

TYPICAL TEST DATA	90	140	250
Flash Point, COC, C° (F°)	245	246	248
Pour Point, C° (F°)	-12	-11	-9
Specific Gravity, API, 60 F°	0.913	0.928	0.943
Gravity, API, 60 F°	23.4	21.0	18.70
Viscosity cSt @ 40°C	220	374	880
SUS @ 100°C	1100	2044	4550

M & J Sunshine, Corp

7391 NW 78 Street Medley FL 33166

Tel:(305) 888 1155 Fax: (305) 888 1157

www.topperlubricants.com