

TOPPER[®]

HIGH-QUALITY MOTOR OIL

TOPPER 4-CYCLE 20W50 MOTOR OIL

TOPPER 4-Cycle 20W-50 motor oil is a premium quality lubricant specially designed to protect motorcycle engines. It is formulated with an additive package chosen for exceptional wear protection, sludge, varnish resistance, and thermal stability. **TOPPER 4-Cycle 20W-50** motor oil is specifically designed for high RPM and high temperature applications to provide maximum performance and protection for 4-stroke engines in motorcycles, ATVs and similar vehicles.

BENEFITS

- Reduces heat, friction, and wear.
- Provides excellent protection for transmissions and wet clutches.
- Outstanding protection against thermal and viscosity breakdown.
- Provides excellent protection for air cooled engines.
- Protects against piston/cylinder scuffing.
- Flows well in cold starts to minimize wear.

RECOMMENDATIONS/SPECIFICATIONS

TOPPER 4-Cycle 20W-50 motor oil is suitable for use where the following specifications are recommended:

- API Classification SL, SJ, SH or SG.
- JASO MA/MA2

APPLICATIONS

TOPPER 4-Cycle 20W-50 motor oil is specifically designed for high RPM and high temperature applications found in 4-stroke engines used in motorcycles, ATVs and similar vehicles.

TOPPER 4-Cycle 20W-50 motor oil Motorcycle Oil can be used in all 4-stroke motorcycle engines including racing, high performance, street and off-road motorcycles.

SPECIAL HANDLING, NOTICES OR WARNINGS

Use the same care and handling as for any petroleum product.
Always consult your owner's manual for proper service.

TOPPER[®]

HIGH-QUALITY MOTOR OIL

TYPICAL TEST DATA 4-CYCLE 20W-50 MOTOR OIL

| Grade SAE | 20W-50 |
|-------------------------------------|---------------|
| Product Name | 4-Cycle |
| Gravity, ASTM D 4052, 'API' 60 °F | 31.7 |
| Low Temperature Viscosity (COC), °C | 6800 @ -15 |
| Viscosity, ASTM D 445, cSt at 100°C | 18 |
| ASTM D 445, cSt at 40°C | 159.20 |
| Viscosity Index, ASTM D 2270 | 125 |
| Pour Point, ASTM D97, °F(°C) | 2.18 |
| Color, ASTM D 1500 (May vary) | 2 |

***PLEASE NOTE: ALWAYS CONSULT YOUR OWNER'S MANUAL FOR YOUR PROPER FLUID EQUIPMENT.**

M & J Sunshine, Corp

7391 NW 78 Street Medley FL 33166

Tel:(305) 888 1155 Fax: (305) 888 1157

www.topperlubricants.com

Page 2 of 2.