

# **TOPPER<sup>®</sup>**

## **HIGH-QUALITY MOTOR OIL**

### **ISO Hydraulic Fluids**

**TOPPER ISO Hydraulic Fluids** are quality hydraulic fluids formulated from base stocks incorporated with select additives designed for high pressure, heavily loaded hydraulic systems.

**TOPPER ISO Hydraulic Fluids** are efficient anti-wear oils, fully inhibited with anti-oxidation, anti-corrosion, anti-rust and anti-foam additives. Superior anti-rust characteristics protect pump lines and controls against rust and corrosion. They exhibit excellent demulsification properties even above moderate temperature levels, still maintaining the ability to reject water.

**TOPPER ISO Hydraulic Fluids** are recommended where higher pressures and increased speeds demand oils with added anti-wear protection. In the proper grade, these fluids may be used in circulation, splash bath and ringed oil systems supplying bearings and gears, as well as hydraulic systems.

	<b>22</b>	<b>32</b>	<b>46</b>	<b>68</b>	<b>100</b>
SAE Grade (Approx)	5	10	20	30	40
Pour Point, °F	-25	-25	-20	-20	-10
Gravity, API, 60°F	29.5	29	28.5	28	27
Viscosity Index (min.)	65	65	65	65	65
Viscosity cSt @ 40°C	22	32	46	68	100
cSt @ 100°C	4.09	4.95	6	7.6	9.7
SUS @ 100°F	-	150	215	315	460
Oxidation, ASTM D-943, hours	>2000	>2000	>2000	>2000	>2000
Color, ASTM (max.)	3	3	3	3.5	3.5

**M & J Sunshine, Corp**  
7391 NW 78 Street Medley FL 33166  
Tel:(305) 888 1155 Fax: (305) 888 1157

[www.topperlubricants.com](http://www.topperlubricants.com)