



NGEO LOW ASH ENGINE OIL Aceite para Motor NGENO Low ASH

NGEO LOW ASH ENGINE OIL

Mecha Tool® NGENO LOW ASH ENGINE OIL is a lubricating oil with a Low content of sulfated ashes. This lubricant meets CUMMINS L10 & M11. Its balanced formula of dispersants and inhibitors provides deposit control and protection against wear, oxidation and oil nitration.

API SERVICE: CF

BENEFITS:

- Controls of machinery high operating temperatures.
- Very low formation of coal deposits which reduces wear.
- Specially designed for engines that work with natural gas, or similar.
- Extends the machinery's life.
- Saves fuel and increases engine power.

APPLICATIONS:

- Four-stroke engines fueled by landfill gas containing elevated levels of chlorofluorocarbons (CFCs).
- Applications in acid gas engines where wear and corrosion is a special concern.
- Engines in which a high level of ash is preferred to improve control of valve recession.
- On engines subject to high pressure and friction.

PACKAGING: 5 Gallon Pail and 55 Gallon drum.



SPECS SHEET MECHA TOOL® NGENO LOW ASH ENGINE OIL

Grade SAE	40	15W-40
Product	LOW ASH	LOW ASH
Gravity, ASTM D 4052, API	27.7	32.1
Flash Point, ASTM D92 (COC), °C	215	225
Viscosity, ASTM D 445, cSt at 100 °C	13.8	15.1
Viscosity, ASTM D 445, cSt at 40 °C	138.1	110.0
Viscosity Index, ASTM D 2270	96	143.0
Pour Point, ASTM D97, °C	-15	-25
Sulfated Ash, ASTM D 874, % Max	0.45	0.45
TBN (total base no.), ASTM D2896	5.1	5.1



Made in U.S.A.

www.mandjsunshine.com