



Locomotive Motor Oil RR ZINC-FREE
Aceite para Locomotora RR ZINC-FREE

LOCOMOTIVE MOTOR OIL RR ZINC-FREE

MECHA TOOL® Locomotive Series RR Zn Free can be use in all current LMOA generations including Generation 6 and Generation 7. Fully approved for use in all locomotive technologies produced by General Electric or Electro Motive Diesel. Designed to meet performance requirement of Tier 4 Locomotives using Ultra Low Sulfur Diesel with less consumption and lower emissions. This Medium Speed Diesel Detergent Formula enables extensions to the lubricant drain intervals.

BENEFITS:

- LMOA GENERATION 6 & 7
- Zinc Free Protection
- Extended oil drain intervals
- Extended Filter life
- Appropriate for high horsepower turbocharged diesel engines

APPLICATIONS:

- General Electric
- Electro Motive Diesel
- Legacy Models like Detroit Diesel, ALCO, Fairbanks Morse Two and Four Cycle, naturally aspirated or turbocharged medium speed diesel engines.

GRADES: SAE 40, 20W-40.

PACKAGING: 5 Gallon Pail and 55 Gallon Drum.



SPECS SHEETS LOCOMOTIVE MOTOR OIL RR ZINC-FREE

SAE	40	20W-40
Viscosity cSt at 40°C	160.38	134.65
Viscosity cSt at 100°C	15.3	15.1
Viscosity Index,	100	115
TBN, mg KOH/kg	10.0	10.0
Pour Point, °F (°C)	-12 (-24)	-17 (-27)
Flash Point, °F (°C)	456 (236)	448 (231)
CCS Viscosity cP @ -15 °C	NA	7,000
Sulfated Ash, Wt%	1.0	1.0
Zinc, ppm	10	10



Made in U.S.A.

www.mandjsunshine.com