#### **MATERIAL SAFETY DATA SHEET**

## **SECTION 1 - IDENTIFICATION**

PRODUCT NAME: Mecha Tool Automatic Transmission Fluid (For use in vehicles previously serviceable by Dexron III ™ / Mercon™ brands).

EMERGENCY TELEPHONE: (305) 888 1155 TRADE OWNER: **M & J Sunshine, Corporation**.

INFORMATION FAX: (305) 888 1157

TRADER ADDRESS: 3200 NW 119<sup>TH</sup> 33167

CHEMICAL NAME OR FAMILY FORMULA: Petroleum Hydrocarbons plus additives Proprietary.

## **SECTION 2 – CHEMICAL AND PHYSICAL PROPERTIES**

BOILING POINT: >626°F (>330 °C) SPECIFIC GRAVITY: 0.87

VAPOR PRESSURE (mm Hg at 20 °C): Nil MELTING POINT: <-40°F (<-49 °C)

VAPOR DENSITY (air = 1): Not Volatile EVAPORATION RATE: Nil

SOLUBILITY IN WATER AT 20 °C: Nil VISCOSITY SUS AT 100 °F:<100 100 or

>

STRONG ACID BASE: Stable pH Asis pH ( ): NDA APPEARANCE AND ODOR: Light viscous liquid, red in appearance, petroleum oil odor

HAZARDOUS DECOMPOSITION PRODUCTS: On burning, carbon monoxide and carbon dioxide, plus oxides

of phosphorus and sulfur.

INCOMPATIBILITY: Strong oxidizers such as hydrogen oxidizer, bromine and chromic acid.

# SECTION 3 - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT AND METHOD USED: 199 °C / 330°F FLAMMABLE LIMITS: Lower: 1% Upper: 10%

EXTINGUISHING MEDIA: Dry, Foam, CO2

SPECIAL FIRE FIGHTING PROCEDURES: Use waterspray to cool fire-exposed surface and to protect personnel UNUSUAL FIRE AND EXPLOSION HAZARDS: Respiratory protection (NIOSH approved) for fire

fighting personnel. Cool with water; no unusual products of combustion.

## **SECTION 4 – HEALTH HAZARD DATA**

 $PERMIISSIBLE\ CONCENTRATIONS\ (air):\ Oil\ Mist,\ mineral\ 5\ mg/m_{\tiny 3}\ PEL\ OSHA,\ 5\ mg/m_{\tiny 3}\ TWA\ ACGIH$ 

ROUTE(S) OF ENTRY: Inhalation? Yes Skin? Limited Ingestion? Yes (deliberate)

HEALTH HAZARDS-ACUTE TOXICOLOGICAL PROPERTIES: NDA Skin: Prolonged contact may cause dermatitis to some extent.

CARCINOGENICITY: None NTP? No IARC Monographs? No OSHA Regulated? No

SIGNS & SYMPTOMS OF EXPOSURE: Eyes: Red and drowsy; dizziness, altered personality, nausea, vomiting.

**EMERGENCY & FIRST AID PROCEDURES:** 

<u>Eyes</u>: Immediately flush with large quantities of water for at least 15 minutes and call a physician if the irritation persists.

Skin: Remove excess with cloth or paper. Wash thoroughly with soap and water.

Inhalation: Remove exposed person to fresh air and ventilate area. Call a physician.

Ingestion: Call a physician. Do NOT induce vomiting. Never give anything by mouth to an unconscious person.

Mecha Tool™ - ATF Page 2 of 2

# **SECTION 5 – CONTROL MEASURES**

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: In significant volume, transfer into container for disposal. Absorb with inert ingredients such as sand/earth/vermiculite: sweep and dispose according to regulations. Prevent liquid from entering sewers, watercourses or low areas. Adequately ventilate area. Recover free liquid by pumping, or use a suitable absorbent (vermiculite).

WASTE DISPOSAL METHOD: Dispose of in accordance with all applicable Federal, State and Local regulations.

PRECAUTIONS FOR HANDLING AND STORING: Keep container closed until ready for use. Keep away from feed and food products. Do not handle or store near flame, high heat or strong oxidizers. Adequate ventilation required. OTHER PRECAUTIONS: Do not store or handle in temperatures above 100°F.

# **SECTION 6 – PRECAUTIONS FOR SAFE HANDLING AND USE**

RESPIRATORY PROTECTIONS: None.

VENTILATION: None.

PROTECTIVE GLOVES: Rubber.

EYE PROTECTION: Chemical safety goggles.

OTHER PROTECTIVE EQUIPMENT/CLOTHING: Usually not needed

WORK/HYGIENIC PRACTICES: Use usual, good hygienic practices; wash thoroughly after use.

#### **SECTION 7 – TRANSPORTATION DATA**

DOT ID No.: N/A DOT LABEL REQUIRED: None

FREIGHT CLASSIFICATION: Petroleum Lubricating Oil

HAZARD CLASS: Nonhazardous PACKING GROUP: N/A

SPECIAL TRANSPORTATION NOTED: None.

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. This

Material Safety Data Sheet was prepared to comply with the OSHA Hazard Communication Standard (29 CFR 1910.1200). This supersedes any previous information.