



Monograde Diesel Engine Motor Oil
Aceite Motores Diesel Monogrado

MECHA TOOL® HD MONOGRADE MOTOR OIL



Mecha Tool® SAE 40 and SAE 50 are manufactured using carefully selected premium high viscosity index base oils combined with a high performance additive package with optimal blending of dispersants, oxidation and corrosion inhibitors, extreme pressure anti-wear, viscosity improver, and de-foaming additives. It is designed for use in both turbo-charged and naturally aspirated diesel and gasoline engines used in automotive, heavy duty trucking, construction, mining and farm equipment.

Mecha Tool® SAE 40 and SAE 50 MOTOR OILS are suitable for use where the following specifications are recommended:

CF-2, CF, CE, CDII, CD, SJ, SH, SG, AND FORMER CCMC, PD-2, AND D-4.

Grades Available SAE 40 and SAE 50.

PACKAGING: 12 Qts Box, 3 GI Box, 5 Gallon Pail, 55 gallon Drum

TYPICAL TEST DATA HEAVY DUTY MOTOR OIL

SAE Grade	40	50
API Classification	CF-2	CF-2
Viscosity cSt at 40°C	149.2	199.6
cSt at 100°C	15.00	18.00
Viscosity Index	101	98
Gravity, API	0.855	0.867
TBN	8.0	8.0
Color D1500	3.5	3.5
Flash Point, °F	220	224
Pour Point, °C	-15	-12



Made in U.S.A.

www.mandjsunshine.com/mecha-tool