

Full Synthetic ATF Fluido Para Transmisión Automática 100% Sintético/ Dexron ®IV

MECHA TOOL[®] FULL SYNTHETIC ATF/DEXRON[®] IV

Mecha Tool[®] Full Synthetic ATF (Automatic Transmission Fluid) DEXRON[®] VI is a premium quality, high performance formulation of 100% synthetic base oils and a sophisticated additive package that meets or exceeds the performance, protection and service requirements of virtually all makes and models of automatic transmission manufactured worldwide. It may also be used for power steering units and hydraulic systems.

Mecha Tool[®] Full Synthetic ATF (Automatic Transmission Fluid) DEXRON[®] VI may be used as a fluid top-off, or for drain-and- fill or flush-and-fill installation. Flush-and-fill provides the greatest benefit as essentially all fluid is replaced.

Mecha Tool[®] Full Synthetic ATF (Automatic Transmission Fluid) DEXRON[®] VI provides the superior performance and protection benefits of synthetic fluids and an advanced additive package for extended life service in transmissions with improved high and low temperature, heavy duty, severe service and anti-wear protection.

Mecha Tool[®] Full Synthetic ATF (Automatic Transmission Fluid) DEXRON [®] VI is manufactured to our AQATM standards of quality control that exceed industry standards. Every batch is laboratory tested from base stocks and additives to finished product, in order to consistently deliver an exceptional level of product quality.

Not to be used in CVT applications.

PACKAGING:12 qts box, 5 gl pail & 55 gl drum.

TYPICAL TEST DATA	
Gravity, ASTM D 4052, API	34.0
Flash Point, ASTM D92 (COC), °F(°C)	400/204
Viscosity, ASTM D 445, cSt at 100°C	6.0
ASTM D 445, cSt at 40°C	28.93
Viscosity Index, ASTM D 2270	158.8
Pour Point, ASTM D97, °F(°C)	-49/-45
Appearance	Red
Brookfield Viscosity cP @ -40°C	10.000

Typical test data are average values only. Minor variations which do not affect product performance are to be expected during normal manufacturing.



www.mandjsunshine.com/mecha-tool