MECHA TOOL
Lubricants

Aceite Mineral para Motores a Gasolina
Gasoline Engine Motor Oil

ACEITE MINERAL PARA MOTORES A GASOLINA



Mecha-tool® Semi-Synthetic SAE **5W-20, 5W-30, 10W-30, 10W-40, 15W-40** & **20W-50** offer superior strength for modern engines operating under high pressures, maximizing performance and efficiency.

- Fights deposits and sludge, improving fuel economy.
- Excellent resistance to thermal breakdown.
- Protects up to the maximum oil change interval recommended by the manufacturer.

Meets or exceeds API SQ/ILSAC GF-7A for increased LSPI protection, improved timing chain wear control, superior cleanliness, and compatibility with TGDI emissions systems. Exceeds more stringent requirements for sulfated ash, oxidation resistance, and fuel economy performance.

PACKAGE: 12-quart case, 3-gallon case, 3/5-quart case, and 55-gallon drum.

INFORMACION TECNICA ACEITE PARA MOTORES A GASOLINA MECHA TOOL®

SAE Grade	5W-20	5W-30	10W-30	10W-40	15W-40	20W-50
Viscosidad cSt at 40°C	51.56	68.77	67.33	108.6	112.5	165.8
cSt at 100°C	8.90	11.42	10.45	15.74	15.30	19.64
Indice de Viscosidad	153	160	143	154	143	136
Densidad @ 15.6 °C	0.8492	0.8561	0.8600	0.8602	0.8656	0.871
Color D1500	2.5	2.5	2.5	2.5	3.0	3.0
Punto de Encendido, °C	203	204	205	205	204	206
Punto de Derrame, °C	-48	-47	-43	-40	-37	-38
Categoría API	Cumple o Excede API SQ & SP, SN, SM, SL, SJ					
ILSAC Certification GF-7A	YES	YES	YES	YES	YES	YES

Made in U.S.A.

www.mandjsunshine.com/mecha-tool

MECHA TOOL Lubricants

Gasoline Engine Motor Oil
Aceite Mineral para Motores a Gasolina

MECHA TOOL® GASOLINE ENGINE MOTOR OIL



Mecha Tool® 5W-20, 5W-30, 10W-30, 10W-40, 15W-40 and 20W-50 are the new detergent formula engineered to provide maximum protection in all weather conditions. **Mecha Tool®** meets or exceeds all automobile and light duty truck warranty requirements for gasoline and turbocharged engines where API SP, SN, SM and ILSAC GF-6 oils are recommended. **Mecha Tool®** can be used in place of SL, SJ, SH and SG rated oils. Follow manufacturer's recommendations for viscosity grade and API Service Category.

Meets or exceeds API Service SP and ILSAC GF-6.
Mecha Tool® 10W-30 meets all requirements for RESOURCE CONSERVING performance standards.
Advanced anti-wear formula to help extend engine life.
High detergency action to help prevent formation of sludge, varnish and rust.
Enhances fuel economy and high protection against thermal breakdown.

PACKAGING: 12 Quart Boxes, 3 Gallon Boxes, 3/5 qts gallon and 55 Gallon Drums.

TYPICAL TEST DATA MECHA TOOL® GASOLINE MOTOR OILS

SAE Grade	5W-20	5W-30	10W-30	10W-40	15W-40	20W-50
Viscosity cSt at 40°C	51.56	68.77	67.33	108.6	112.5	165.8
cSt at 100°C	8.90	11.42	10.45	15.74	15.30	19.64
Viscosity Index	153	160	143	154	143	136
Gravity, API	0.8492	0.8561	0.8600	0.8602	0.8656	0.871
Color D1500	2.5	2.5	2.5	2.5	3.0	3.0
Flash Point, °F	203	204	205	205	204	206
Pour Point, °C	-48	-47	-43	-40	-37	-38
API Service	Meet or Exceed API SQ & SP and SN, SM, SL, SJ, SH					
API "Resource Conserving"	YES	YES	YES	YES	YES	YES
ILSAC Certification GF-7A	YES	YES	YES	YES	YES	YES

Made in U.S.A.

www.mandjsunshine.com/mecha-tool