



MECHA-TOOL® Full Synthetic AW-68

MECHA-TOOL® Full Synthetic AW-68 Hydraulic Fluid is a high quality hydraulic fluid specially formulated to provide extreme protection against wear and corrosion, thermal stability, oxidative and good filtration capacity. **MECHA-TOOL® Full Synthetic AW-68 Hydraulic Fluid** is designed in high quality synthetic bases and selected additives for high pressure and heavy load hydraulic systems. Oxidation stability 10,000 hours. **MECHA-TOOL® Full Synthetic AW-68 Hydraulic Fluid** contains inhibited additives with antioxidants, anti-corrosives and anti-foam. Its high viscosity index protects the equipment at high and low temperatures. CM P-68, P-69 AND P-70, Dennison HF-O, HF-1 AND HF-2.

Applications:

- USS 136, 127
- DIN 51524 Part II
- CM P-68
- P- 69 and P-70
- Dennison HF-O, HF-1 and HF-2



ISO-Viscosity Grade	68
API Gravity @60°F	37.42
Visc cSt @ 40°C.,	65.070
Visc cSt @ 100°C	10.156
Viscosity Index	142.0
Flash Point, COC, °C	259
Oxidation Stability, hrs	>10,000
Pour Point , °C	-30
Color, ASTM D-1500	L1.0

M & J Sunshine, Corp

7391 NW 78 Street Medley FL 33166

Tel:(305) 888 1155 Fax: (305) 888 1157 www.mandjsunshine.com