



**Gasoline Engine Full Synthetic Motor Oil**  
**Aceite 100% Sintético Motores a Gasolina**

**MECHA TOOL FULL SYNTHETIC MOTOR OIL**

**Mecha Tool Full Synthetic** Motor Oils meet the latest automotive manufacturers requirements of API SP. **Mecha Tool Full Synthetic** Motor Oils 0W-20, 5W20, 5W30 and 10W30 meet **ILSAC GF-6A** requirements for use in passenger car engines. **Mecha Tool Full Synthetic** Motor Oils show improved high temperature deposit control, oil consumption and improvements in fuel economy. The 0W-20, 5W-20, 5W-30 and 10W-30 have a better low-temperature pump ability and lower volatility when compared with motor oils meeting other API classifications.

**Mecha Tool** Motor Oils, through the use of highest quality base stocks and up to date additive technology, are formulated to provide the highest levels of equipment protection available. **Mecha Tool Full Synthetic** Motor Oils provide:

- Excellent Fuel Economy.
- Excellent volatility for low oil consumption.
- Excellent protection from deposits at all operation temperatures.
- Excellent anti-wear, anti-foam, bearing corrosion and anti-rust protection.
- Excellent cold cranking capabilities.

**Mecha Tool Full Synthetic** Motor Oils may be recommended for the following uses:

- When SP, SN, SM, SL, SJ, SH, SG, SF, SE, SD, or SC oils are required.
- When former MIL L 46152D and CID AA 52039B performance level is required.
- When GM 6094M, Ford M2C929A, Ford WSS-M2C930-A, M2C153H and Chrysler MS 6395M oils are required.
- Meets both domestic and foreign car manufacturers requirements.
- Resource Conserving motor oil (0W-20, 5W-20, 5W-30, 10W-30)
- ILSAC GF-6A Certified (0W-20, 5W-20, 5W-30, 10W-30)
- Grades 0W-20 and 5W-30 meet DEXOS™ 1 Gen 3™ requirements.

**PACKAGING:** 12 Quart Boxes, 3/5 qts gallons, 55 Gallon Drums.



**CERTIFICACION GM**



**TYPICAL PROPERTIES FULL SYNTHETIC MOTOR OIL**

SAE Grade	0W-20	5W-20	5W-30	10W-30
Viscosity cSt at 40°C	47.56	48.71	66.11	63.98
cSt at 100°C	8.90	8.90	11.5	10.53
Viscosity Index	170	165	170	154
Gravity, API	0.8464	0.8466	0.8475	0.8500
Color D1500	2.5	2.5	2.5	2.5
Flash Point °F	204	204	204	207
Pour Point, °C	-47	-44	-37	-38
ILSAC Certification (GF-6A)	YES	YES	YES	YES
Dexos™ 1 Gen 3 Certification	YES	NO *	YES	NO *

\* General Motors authorizes Dexos™ 0W-20 to be used in engines that originally use 5W-20 and those that require 10W-30 may use 5W-30.



Made in U.S.A.

[www.mandjsunshine.com/mecha-tool](http://www.mandjsunshine.com/mecha-tool)