TOPPER MOTOR OIL

5W-20, 5W-30, 10W-30, 10W-40, 20W50, 30, 40

TOPPER Motor Oils meet the latest automotive manufacturers' requirements of API SP, SN / SM, SL. **TOPPER** Motor Oil 5W20, 5W30 and 10W30 meet **ILSAC GF-**6A requirements for use in passenger car engines. **TOPPER** Motor Oils show improved high temperature deposit control, oil consumption and improvements in fuel economy. The 5W-20, 5W-30, and 10W--30 have a better low-temperature pump ability and lower volatility when compared with motor oils meeting other API classifications.

Grades 5W-20, 5W-30 and 10W-30 are semi-synthetic motor oils.

TOPPER Motor Oils, through the use of highest quality base stocks and up to date additive technology, are formulated to provide the highest levels of equipment protection available. TOPPER Motor Oils provide:

- Excellent Fuel Economy.
- Excellent volatility for low oil consumption.
- Excellent protection from deposits at all operation temperatures.
- Excellent anti-wear, anti-foam, bearing corrosion and anti-rust protection.
- Excellent cold cranking capabilities.

TOPPER Motor Oils may be recommended for the following uses:

- When SP, SN, SM, SL, SJ, SH, SG, SF, SE, SD, or SC oils are required.
- When former MIL L 46152D and CID A A 52039B performance level is required.
- When GM 6094M, Ford M2C929A, Ford WSS-M2C930-A, M2C153H and Chrysler MS 6395M oils are required.
- Meets both domestic and foreign car manufacturers' requirements.
- Resource Conserving motor oil (5W20, 5W30, 10W30)
- ILSAC GF-6A Certified (5W20, 5W30, 10W30)

TOPPER Motor Oils are available in 5 multi-viscosity grades to comply with most passenger car and light duty truck engine applications.

TYPICAL PROPERTIES

SAE GRADE	5W-20 SEMI SYNTHETIC	5W-30 SEMI SYNTHETIC	10W-30 SEMI SYNTHETIC	10W-40	20W-50	SAE 30	SAE 40
Viscosity cSt@40 oC	48	60.5	68.7	97	160	101.5	155
cSt@ 100 ºC	8.1	10.0	10.5	13.8	18.5	10.9	14.4
Viscosity Index	140	144	140	145	130	90	80
Gravity, API	32.5	32.5	31.5	31.5	30	31.5	31
Pour Point, ºF	-33	-33	-17	-11	-11	-33	-22
Pour Point, ºC	-36	-36	-27	-24	-24	-36	-30
API Service	Licensed for SN and also meets SM,SL, SJ, SH						
API "Resource Conserving"	YES	YES	YES	NO	NO	NO	NO
ILSAC Certification GF-5	YES	YES	YES	NO	NO	NO	NO

MADE IN U.S.A.

**PLEASE NOTE: ALWAYS CONSULT YOUR OWNER'S MANUAL FOR YOUR PROPER FLUID EQUIPMENT.*

www.mandjsunshine.com/topper
Worldwide Represented by: M & J SUNSHINE, CORP. MIAMI, FL 33166 / FAX: (305) 888 1157