



## **5W-40 Euro-Power Full Synthetic**

**Topper® 5W-40 Euro-Power Full Synthetic** meets the latest automotive manufacturers' requirements of ACEA A3/B3, ACEA A3/B4 and ACEA A5/B5 **Topper® Euro-Synthetic Formula Motor Oils** show improved high temperature deposit control, oil consumption and improvements in fuel economy.

**Topper® Euro-Synthetic Formula Motor Oils. Topper® Euro-Synthetic Full Synthetic Formula Motor Oils** provide:

- Complies with API Service CK-4 / SN for diesel and gasoline engines.
- Excellent Fuel Economy.
- Excellent volatility for low oil consumption.
- Excellent protection from deposits at all operation temperatures.
- Excellent anti-wear, anti-foam, bearing corrosion and anti-rust protection.
- Excellent cold cranking capabilities.

**Topper® Euro-Synthetic Full Synthetic Formula Motor Oils** may be recommended for the following quality levels:

- Meets ACEA A3/B3, A3/B4, C3
- BMW LL-04
- Mercedes Benz 229.3, 229.5
- Porsche A40.
- Volkswagen 502.00 & 505.00
- Renault RN 0700, 0710
- JASO MA2(T903-2011)
- API CK-4/SN
- When former MIL L 46152D and CID A A 52039B performance level is required.
- When GM 6094M, Ford M2C929A, Ford WSS-M2C930-A,
- Meets both domestic and foreign car manufacturers' requirements.

**PLEASE NOTE: ALWAYS CONSULT YOUR OWNER'S MANUAL FOR YOUR PROPER FLUID EQUIPMENT.** Page 1 of 2.

# **TOPPER<sup>®</sup>**

**HIGH-QUALITY MOTOR OIL**

## **5W-40 Euro-Power Full Synthetic**

|                              |          |            |              |
|------------------------------|----------|------------|--------------|
| DESCRIPCION                  |          |            |              |
| GRADO SAE                    |          |            | <b>5W-40</b> |
| API Service                  |          |            | CK-4/SN      |
| Density 15°C                 | g/ml     | ASTM D4052 | 0.863        |
| Viscosity 100°C              | cSt      | ASTM D445  | 15.00        |
| Viscosity 40°C               | cSt      | ASTM D445  | 92.7         |
| Viscosity Index              | -        | ASTM D2270 | 171          |
| Flash Point                  | °C       | ASTM D92   | 220          |
| Pour Point                   | °C       | ASTM D97   | -40          |
| TBN                          | Mg KOH/g | ASTM D2896 | 8            |
| Volatility Noack, 1 Hr 250°C | % wt     | ASTM D5800 | 10           |
| Gravity °API                 |          | ASTM D4052 | 34.1         |

**M & J Sunshine, Corp**

3200 NW 119<sup>TH</sup> ST, Miami, Florida

Tel: (305) 888 1155 Fax: (305) 888 1157

[www.topper.com](http://www.topper.com)

Page 2 of 2.