



TOPPER® 2-CYCLE MOTOR OIL

Topper® 2-Cycle Motor Oil is formulated for use in air cooled 2-cycle engines.

Features/Benefits:

- Provides easy starts.
- Provides anti scuff and anti wear protection.
- Protect against rust and corrosion.
- Minimizes deposits.
- Controls plug fouling.

Precautions

The same care and handling as for any petroleum-derived product. Always check user's manual and for the appropriate service.

Aplicaciones:

- Air cooled 2 cycles engines
- Engines calling for API TC performance level oil.
- Suitable for use in following 2-cycle engines:
 - Homelite
 - Husqvarna
 - Poulan
 - Pioneer
 - Stihl
 - McCulloch

TYPICAL TEST DATA	ACEITE 2- TIEMPOS
SAE GRADE	30
FLASH POINT, COC C° F°	207/405
POUR POINT C° F°	-18/0
COLOR	3,5
GRAVITY, API 60° F	23.0
VISCOSITY CST @ 40°	52.8
SUS @ 100 °	8.5



MADE IN U.S.A.



*ALWAYS FOLLOW THE MANUFACTURER VEHICLE LUBRICATION RECOMENDATIONS.

www.mandjsunshine.com/topper

Representado Mundialmente por: M & J SUNSHINE, CORP. Miami, FL 33166 / FAX: (305) 888 1157