



**REIKER Full Synthetic Motor Oils formula UL**

**REIKER Full Synthetic Motor Oils Formula UL** provides superb performance for today's gasoline powered cars, light trucks, and vans. They are formulated with outstanding synthetic base oil to provide clean engines and excellent control of sludge and other engine deposits that form because of high engine temperatures and combustion exhaust. Selected anti-wear additive are used to reduce wear and extend the engine life.

**REIKER Full Synthetic Motor Oils Formula UL** meets the requirements Service category SP. **REIKER** 0W-20, 5W-20, 5W-30, 10W-30 and 10w-40 Motor Oils are full synthetic formulas and meet ILSAC GF-6A requirements for use in passenger car engines.

**REIKER Full Synthetic Motor Oils Formula UL** have a very high Viscosity Index which reduces wear in high temperature weathers.

**REIKER Full Synthetic Motor Oils Formula UL** are specially engineered for today's high temperature, high revving performance engines.

<b>REIKER FULL SYNTHETIC Formula UL Typical Properties</b>					
SAE Grade	0W-20	5W-20	5W-30	10W-30	10W-40
Viscosity					
@40° C. cSt	47.56	48.71	48.69	64.96	63.98
@100°C, cSt	8.90	8.90	8.47	10.3	10.53
Viscosity Index	170	165	151	146	154
Pour Point, °C	-47	-44	-37	-40	-38
Flash Point, °C	204	204	204	208	207
ASTM Color (max.)	2.5	2.5	2.5	2.5	2.5

**M & J Sunshine, Corp.**  
 3200 NW 119<sup>TH</sup> ST, Miami Florida 33167  
 Tel: (305) 888 1155  
[www.mandjsunshine.com](http://www.mandjsunshine.com)

