



MECHA-TOOL F-10 Motor Oil

SYNTHETIC BLEND 15W-40 CK-4/SN, CJ-4

Mecha-tool Synthetic Blend 15W-40 CK-4/SN is developed for use in high-speed four-stroke cycle diesel engines designed to meet 2017 model year on-highway and Tier 4 non-road exhaust emission standards as well as for previous model year diesel engines. These oils are formulated for use in all applications with diesel fuels ranging in sulfur content up to 500 ppm (0.05% by weight). These oils are especially effective at sustaining emission control system durability where particulate filters and other advanced after-treatment systems are used. **Mecha-tool Synthetic Blend 15W-40 CK-4/SN** oils are designed to provide and **Mecha-tool Synthetic Blend 15W-40 CK/SN** exceed the performance criteria of API CJ-4, CI-4 PLUS, CI-4, and CH-4 and can effectively lubricate engines calling for those API Service Categories. When using **Mecha-tool Synthetic Blend 15W-40 CK-4/SN** oil with higher than 15 ppm sulfur fuel, consult the engine manufacturer for service interval recommendations.

Mecha-tool Synthetic Blend 15W-40 CK-4 provide:

- Enhanced protection against oil oxidation and viscosity loss due to shear.
- Enhanced protection against oil aeration and catalyst poisoning,
- Enhanced protection against particulate filter blocking, engine wear,
- Enhanced protection against piston deposits and degradation of low- and high-temperature properties.
- Enhanced protection against soot-related viscosity increase.

Mecha-tool Synthetic Blend 15W-40 CK-4/SN may be recommended for the following quality levels:

- Mack EOS-4.5/Volvo VDS-4.5/Renault RLD-4
- Detroit 93K222
- Cummins 20086

PLEASE NOTE: ALWAYS CONSULT YOUR OWNER'S MANUAL FOR YOUR PROPER FLUID EQUIPMENT.



MECHA-TOOL F-10 Motor Oil

SYNTHETIC BLEND 15W-40 CK-4/SN, CJ-4

DESCRIPTION			
SAE GRADE			15W-40
DENSITY 15°C	g/ml	ASTM D4052	0.8679
VISCOSITY 100°C	cSt	ASTM D445	15.99
VISCOSITY 40°C	cSt	ASTM D445	120.69
VISCOSITY -20°C	cP	ASTM D5293	5800
VISCOSITY INDEX	-	ASTM D2270	141
FLASH POINT OPEN CUP	°C	ASTM D92	220
POUR POINT	°C	ASTM D97	-35
TBN	Mg KOH/g	ASTM D2896	10
NOACK VOLATILITY, 1 Hr 250°C	% wt	ASTM D5800	10
HTHS VISCOSITY 150°C	cP	ASTM D4683	4.1

M & J Sunshine, Corp
3200 NW 19TH MIAMI FLORIDA 33167
Tel:(305) 888 1155

www.mandjsunshine.com

Page 2 of 2.