



TOPPER[®]
HIGH-QUALITY LUBRICANTS

OIL TOPPER FOR COMPRESSORS (ISO46) 100% SYNTHETIC

Topper High-performance synthetic base and a special additive package. This lubricant is formulated for Rotary Screw air compressors and under normal operating conditions provides 10,000 hours of work. Drastically protects against friction and premature wear. This oil is not intended for use in food processing plant applications.

BENEFITS:

- High Viscosity Index (HVI)
- Excellent cooling properties.
- Energy savings.
- Excellent rust and corrosion control.
- Reduce downtime
- Reduced maintenance cost
- Excellent oxidation stability
- Carbon and Varnish Control
- Screw Compressors

APPLICATIONS:

Rotary Screw
PRODUCT LIFE 10,000 HOURS

Presentation:

5 gal pail and 55 gal tank.

DATA SHEETS

GRADO SAE	Method test	MIN	MAX	MAX
Pour point, °C	ASTMD445	-	-35	-45
Flash point, °C	ASTMD92	220	-	230
Viscosity Index (min)	ASTM-D445	-	-	169.9
Viscosity cSt @ 40 °C	ASTM-D445	41.4	50.6	49.0
Viscosity cSt @100 °C	ASTM,-D455	-	-	90.1
Specific Gravity 15.6 ° C	ASTMD4052B	-	-	0.8467
Color	VISUAL	-	-	VERDE



MADE IN U.S.A.



www.mandjsunshine.com/topper

Fabricado por : M & J SUNSHINE, CORP. Miami, FL 33167