



## Aceite de tractor hidraulico Mecha-Tool® Tractor Hydraulic Fluid

# TRACTOR HYDRAULIC FLUID

**Mecha Tool Tractor Hydraulic fluid** for tractor transmission and hydraulic oils are unique oils developed with premium additives and bases to meet the exact needs of tractors utilizing tractor hydraulic fluid.

**Mecha Tool Tractor Hydraulic** has been performance tested both in the lab and in the field, and validated to meet the increased demands for performance and protection of transmissions and hydraulic systems.

#### Benefits:

- Reduces wet-brake chatter and ensures high braking capacity.
- Superior wet-clutch performance, smoothes clutch operation.
- High tolerance to water contamination without sludge formation, which could cause filter clogging and hydraulic system malfunction.
- The anti-oxidation capability allows the oil to work properly at high temperatures, helping keep transmissions and hydraulic system parts cool and clean.
- Provides protection against rust and corrosion, particularly during low-use periods.
- Anti-wear additives keep gear and bearing wear to a minimum.
- The extreme-pressure formulation develops a durable fluid film, which helps prevent metal-to-metal contact.

**Mecha Tool Tractor Hydraulic Fluid** is designed to satisfy the tractor hydraulic fluid (THF) performance requirements of:

ALLIS CHALMERS PF-821XL, ALLISON C-3, CATERPILLAR TO-2, DENISON HF-0, DEUTZ HTF, FORD/NEW HOLLAND(M2C41-B, M2C53-C, M2C86-B, M2C134-B, M2C134-C, M2C134-D), INTERNATIONAL HARVESTER, JI CASE(JIC 143, 144, 145, 185, MS-1204, MS-1205), JOHN DEERE(J20-A, J20-C, J20-D, J14-B, J14-C, J21-A, 303), GL-4, KUBOTA UDT &UDT SUPER, MASSEY FERGUSON(M-1110, M-1127, M-1129, M-1135), OLIVER TYPE 55, RENK DOROMAT ATF, VICKERS, SAUER SUNSTRAND, SPERRY VICKERS, STEIGER HYDRAULIC TRANS FLUID, SUNSTRAND HMS-103, VERSATILE GEAR/HYDRAULIC TRANS FLUID, FIAT-HESSTON, LANDINI, WHITE Q1722 &Q1826.



#### Tractor Hydraulic Fluid

Grade SAE (Approx)	10W-20/30
Dropping Point, °F	-45
API Gravity, 60°F	30.3
Viscosity Index (min.)	137
Viscosity cSt @ 40°C	61
SUS @ 100°F	9.5
Flash Point°C	200
Brookfield Vis, cP @ -20°C/-35°C max	5500/70,000



Made in U.S.A.

[www.mandjsunshine.com](http://www.mandjsunshine.com)



*Aceite para tractor hidraulico*  
**Mecha-Tool® Tractor Hydraulic Fluid**

## ACEITE PARA TRACTOR HIDRAULICO

**Mecha Tool Tractor Hydraulic fluid** for tractor transmission and hydraulic oils are unique oils developed with premium additives and bases to meet the exact needs of tractors utilizing Los Fluidos Hidráulicos para Tractores **Mecha Tool** son una fórmula incorporada con selectos aditivos, combinados a bases seleccionadas. Puede ser utilizado en maquinaria para la agro-industria sujeta a severos ambientes de trabajo. Esta diseñado para ser utilizado donde hay bombas de trabajo en comun o donde se requiere un solo tipo de fluido para la motricidad, transmision, diferencial o unidades de poder y sistemas de frenos humedos.

Puede ser utilizado donde se requieran cualquiera de los siguientes fluidos:

ALLIS CHALMERS PF-821XL, ALLISON C-3, CATERPILLAR TO-2, DENISON HF-0, DEUTZ HTF, FORD/NEW HOLLAND(M2C41-B, M2C53-C, M2C86-B, M2C134-B, M2C134-C, M2C134-D), INTERNATIONAL HARVESTER, JI CASE(JIC 143, 144, 145, 185, MS-1204, MS-1205), JOHN DEERE(J20-A, J20-C, J14-B, J14-C, J21-A, 303), KUBOTA UDT &UDT SUPER, MASSEY FERGUSON(M-1110, M-1127, M-1129, M-1135), OLIVER TYPE 55, RENK DOROMAT ATF, STEIGER HYDRAULIC TRANS FLUID, SUNSTRAND HMS-103, VERSATILE GEAR/HYDRAULIC TRANS FLUID, WHITE Q1722 &Q1826.



### ACEITE PARA TRACTOR HIDRAULICO

Grado SAE	10W-20/30
Punto de Goteo, °F	-45
Gravedad API, 60°F	30.3
índice de viscosidad	137
Viscosity cSt @ 40°C	61
SUS @ 100°F	9.5
Punto de Quemado °C	200
Brookfield Vis, cP @ -20°C/-35°C max	5500/70,000



Made in U.S.A.

[www.mandjsunshine.com](http://www.mandjsunshine.com)