

TOPPER[®]

HIGH-QUALITY MOTOR OIL

Topper[®] GL-1 Gear Oils SAE 90 and SAE 140 are blended from tested select base stocks, giving the highest protection to your equipment and bearing needs. They are blended from selected Mid. V.I. base stocks and every batch produced is fully tested before packing it. They may contain oxidation, rust and corrosion inhibitors, anti-foam agents and pour point depressants. **Topper[®] GL-1 Gear Oils** do not contain friction modifiers or extreme pressure additives.

Packaging: 12 quarts box, 3 gallon box, 35 Lb. Pail, 120 Lb. Keg and 400 Lb. Drum.

TYPICAL TEST DATA GL-1 GEAR OIL

GRADE	90	140	250
Flash Point, (COC), °F(°C)	470/245	475/246	480/248
Pour Point, °C(°F)	-12/10	-11/12	-9/15
Specific Gravity, API, 60 °F	0.913	0.928	0.943
API Gravity, 60 °F	23.4	21.0	18.70
Viscosity cSt at 40°C	220	374	880
SUS @ 100°C	1100	2044	4550

***NOTE: ALWAYS FOLLOW YOUR VEHICLE MANUFACTURER'S LUBRICATION RECOMMENDATIONS.**

M & J Sunshine, Corp
3200 NW 119TH MIAMI-FLORIDA
Tel:(305) 888 1155

www.manjsunshine.com

Página 2 of 2.