



Heavy Duty SAE 50 Heavy Duty Engine Oil

Mecha-Tool SAE 50 Heavy Duty engine oil is manufactured using the most select base stocks, which in combination with additive packages, produce a formula with optimum dispersant levels, oxidation and corrosion levels for different climates. It contains extreme pressure anti-friction, viscosity increasers and anti-foam additives.

Mecha-Tool SAE 50 Heavy Duty engine oil is recommended for use in moderate working environments and in different climates. It is designed to work not only in Turbo-Diesel engines, but also in gasoline engines in cars, trucks, construction, mining and agricultural farms.

Mecha-Tool SAE 50 Heavy Duty engine oil is recommended to work under the following specifications: API CD.

Performance Capability:

Typical service for some naturally aspirated, turbocharged or supercharged diesel engines in severe duty when using fuels of a wide range of quality, including high sulfur fuels, where effective control against wear and deposits are highly vital.



TECHNICAL SPECIFICATIONS

Grado SAE		50
Product name		SAE 50
Gravity, ASTM D 4052, 'API	60 'F	0.8503
Flash Point, ASTM D92 (COC) (°C)		220
Viscosity, ASTM D 445, cSt at 100°C		17.90
ASTM D 445, cSt at 40°C		153
Viscosity Index, ASTM D 2270		130
SUS @ 100°F		92.33
Pour point, ASTM D97, 'F(°C)		-15
Sulphated Ash, ASTM D 874, % Max		1.5
TBN (total base no., ASTM D2896)		7.0
Color, ASTM D 1500 (Puede variar)		2.5

***NOTE: ALWAYS FOLLOW YOUR VEHICLE MANUFACTURER'S LUBRICATION RECOMMENDATIONS.**

M & J Sunshine, Corp
 3200 NW 119th Street Miami FL 33167
 Tel:(305) 888 1155

www.mandjsunshine.com