



## **PRODUCT DATA SHEET**

### **MOTION-PLUS™ FUEL TREATMENT**

For Gasoline & Diesel Engines

#### **General Information**

- Cleans entire fuel system, improving fuel flow to the ignition system.
- Blends with all grades of leaded, unleaded & diesel fuels.
- Complies with Federal sulfur content requirements for use in diesel engines.
- Contains **MOTION-PLUS™ Engine Treatment** technology for improved upper cylinder lubrication.

#### **Typical Applications**

- Gasoline & diesel engines.
- Small engines, including 2-cycle.
- Also recommended for bulk fuel storage tanks & fuel oil heating systems

#### **Key Features & Benefits**

- Cleans & protects fuel system
- Increases mileage
- Reduces harmful emissions
- Increases atomization in carburization & fuel injection
- Assists in neutralizing combustion acids
- Blasts upper cylinder carbons and provides upper cylinder lubrication
- Cleans & frees stick valves
- Disperses water in the fuel
- Controls algae, jelling & waxing in diesel fuels
- Provides quicker starts in cold temperatures
- Safe for catalytic converters
- Complies with Federal sulfur content requirements
- E-15 compatible

#### **Availability**

- 4-oz. bottle (118.5 ml)
- 32-oz. bottle (948 ml)
- 1 & 5 U.S. gallon containers (3.8 & 18.9 L)
- 55 U.S. gallon drum (208 L)

#### **Directions for Use**

- General: For best results, add **MOTION-PLUS™ FUEL TREATMENT** to the fuel tank prior to refueling. **MOTION-PLUS™ FUEL TREATMENT** will easily blend with the fuel.
- Gasoline & Diesel Engines: For initial treatment, add 4 oz. of **MOTION-PLUS™ FUEL TREATMENT** for every 21 gallons of fuel. For follow-up treatments, add 1 oz. for every 10 gallons of fuel at every fill up.
- In temperatures below 32°F (0°C), continuously use 2 oz. of **MOTION-PLUS™ FUEL TREATMENT** for every 10 gallons of fuel for best results.
- 2 & 4-Cycle Engines: Add 2 oz. of **MOTION-PLUS™ FUEL TREATMENT** to 5 gallons of fuel. For high-performance engines, add 4 oz. to 5 gallons of fuel.

**NOTE:** For 2-cycle engines, be sure to continue using the oil mixture as recommended by the equipment's manufacturer.



### Typical Properties

Boiling Point ..... 176°F (80°C)  
Flash Point ..... 45°F (7.2°C) D93  
Specific Gravity @ 60°F, g/cm<sup>3</sup> ..... 0.8012  
Evaporation Rate (nBuAc = 1)..... ~ 1.5  
Vapor Pressure ..... 1.125 PSI  
Vapor Density (Air = 1) ..... ~ 2  
Viscosity @ 40°C, cSt ..... 2.29  
Freezing Point ..... - 1.5°F (- 18.6°C)  
Odor ..... Petroleum / alcohol  
Color & appearance ..... Light green liquid  
Solubility in Water ..... Partial

### Health & Safety

Flammable liquid. Please refer to Safety Data Sheet for health and safety information prior to use.

### M & J Sunshine, Corp

7391 NW 78 Street Medley FL 33166

Tel:(305) 888 1155 Fax: (305) 888 1157 [www.motion-plus.com](http://www.motion-plus.com)