TOPPER®
HIGH-QUALITY MOTOR OIL

SAE 50 Heavy Duty Engine Oil

Topper SAE 50 Heavy-Duty Engine Oil is manufactured using the finest base stocks, which, combined with additive packages, produce a formula with optimal dispersant levels, oxidation resistance, and corrosion resistance for different climates. It contains extreme pressure antifriction, viscosity increasers, and anti-foam additives.
TOPPER SAE 50 Heavy-Duty Engine Oil is recommended for use in moderate operating environments and in a variety of climates. It is designed to work not only in turbo-diesel engines, but also in gasoline engines in cars, trucks, construction, mining, and agricultural applications.
TOPPER SAE 50 Heavy-Duty Engine Oil is recommended for use under the following specifications: API CD.

Performance Capability: Typical service for some naturally aspirated, turbocharged, or supercharged diesel engines in severe duty applications using a wide range of fuel qualities, including high-sulfur fuels, where effective wear and deposit control are vital.

TOPPER®

HIGH-QUALITY MOTOR OIL

SPEC SHEETS

SAE GRADE		50
Product Name		SAE 50
Gravity, ASTM D 4052, API	60 'F	0.8503
Flash Point, ASTM D92 (COC) (˚C)		220
Viscosity, ASTM D 445, cSt at 100'C		17.90
ASTM D 445, cSt at 40°C		153
Viscosity Index, ASTM D 2270		130
SUS @ 100°F		92.33
Pour Point, ASTM D97, 'F('C)		-15
Sulfated Ash, ASTM D 874, % Max		1.5
TBN (total base no., ASTM D2896)		7.0
Color, ASTM D 1500 (May vary)		2.5

***NOTE: ALWAYS FOLLOW YOUR VEHICLE MANUFACTURER'S LUBRICATION RECOMMENDATIONS.**

M & J Sunshine, Corp
3200 NW 119th Street Miami FL 33167
Ph:(305) 888 1155
www.mandjsunshine.com