REIKER® LUBRICANTS

REIKER® FULL SYNTHETIC MOTOR OIL UL



MADE IN USA

REIKER® 0W-20 FULL SYNTHETIC MOTOR OIL is specially formulated to help improve fuel economy compared with conventional motor oils. Its advanced formula delivers outstanding engine protection and dependable performance. Excellent protection against thermal breakdown under high-temperature operating conditions. Effective control against the formation of sludge and harmful engine deposits. Reliable performance throughout the maximum oil-change interval recommended in your vehicle owner's manual.

Suitable for use where API Service Categories SQ, SP, SN, SM, SL/ILSAC GF-7A and earlier categories are recommended. Always follow the engine manufacturer's recommendations regarding viscosity grade and API Service Category. Designed for use in engines calling for dexos®1 Gen 3 performance.

WARNING: Prolonged or repeated contact with used engine oil has caused skin cancer in laboratory animals. If contact occurs, wash the affected area thoroughly with soap and water. Do not pollute. Conserve resources.

PACKAGING: 12 × 1-quart box, 3 × 5-quart box, and 55-gallon drum.

EL ACEITE PARA MOTOR 100% SINTÉTICO REIKER® 0W-20 está especialmente formulado para ayudar a mejorar el rendimiento del combustible en comparación con los aceites para motor convencionales.

Excelente protección contra la degradación térmica en condiciones de operación a altas temperaturas. Control efectivo contra la formación de lodos y depósitos dañinos en el motor. Rendimiento confiable durante todo el intervalo máximo de cambio de aceite recomendado en el manual del propietario de su vehículo.

Adecuado para su uso donde se recomiendan las categorías de servicio API SQ, SP, SN, SM, SL/ILSAC GF-7A y anteriores. Siempre siga las recomendaciones del fabricante del motor respecto al grado de viscosidad y la categoría de servicio API. Formulado para uso en motores donde se recomienda un desempeno dexos®1 Gen 3.

ADVERTENCIA: El contacto prolongado o repetido con aceite de motor usado ha provocado cáncer de piel en animales de laboratorio. En caso de contacto, lave minuciosamente la zona afectada con agua y jabón. No contamine. Conserve los recursos.

PRESENTACIÓN: Cajas de 12 × 1 cuarto, 3 × 5 cuartos y tambor de 55 galones.

TEST	REFERENCE	0W-20	5W-20	5W-30	10W-30	10W-40	20W-50
APPEARANCE	VISUAL	B&C	B&C	B&C	B&C	B&C	B&C
VISC @ 40°C cST	ASTM D7042	47.33	55.344	61.317	65.89	90.19	163.8
VISC @ 100°C cST	ASTM D7042	8.1002	8.9324	10.571	10.74	14.34	18.09
VISCOSITY INDEX	ASTM D7042	140.8	140	163.2	153	165	123
DENSITY GR/ML	ASTM D7042	0.8678	0.8637	0.8484	0.852	0.8521	0.88
COLOR	ASTM D1500	L3.0	L3.0	L3.0	L3.0	L3.0	L3.0
POUR POINT, °C	ASTM D97	−45	−45	−42	−39	−35	−30
FLASH POINT (COC), °C	ASTM D92	236	231	242	205	209	207
CCS @ ___ °C, cP	ASTM D5293	5,829 (−35 °C)	3,596 (−30 °C)	3,886 (−30 °C)	4,137 (−25 °C)	3,872 (−25 °C)	8,314 (−15 °C)

M&J SUNSHINE CORP. We Speak Engines
590 W 83 ST HIALEAH FL 33014
WWW.MANDJSUNSHINE.COM
@mandjsunshine